

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 May 2005 (12.05.2005)


PCT

(10) International Publication Number
WO 2005/041786 A1

- (51) International Patent Classification⁷: **A61B 17/16** [GB/GB]; 5 Hawthorne Way, Shelley, Huddersfield HD8 8JX (GB).
- (21) International Application Number: PCT/GB2004/003917 (74) Agent: **BELCHER, Simon, J.**; Urquhart-Dykes & Lord, Tower North Central, Merrion Way, Leeds LS2 8PA (GB).
- (22) International Filing Date: 15 September 2004 (15.09.2004) (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0323478.8 8 October 2003 (08.10.2003) GB
- (71) Applicant (*for all designated States except US*): **DEPUY INTERNATIONAL LIMITED** [GB/GB]; St Anthonys Road, Beeston, Leeds LS11 8DT (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **DOWER, Liam** (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: A CUTTING TOOL FOR USE IN ORTHOPAEDIC SURGERY



(57) Abstract: A cutting tool for preparing a cavity in a bone for receiving a component of an orthopaedic joint prosthesis. The shape of the tool is based on a shell having a rotationally symmetrical outer surface. The tool has at least one portion cut out from it, the cut out portion extending from the peripheral edge of the shell toward the pole of the shell, such that the tool has no more than one plane of symmetry passing through the axis of rotation. The external surface of the shell presents at least two outwardly directed cutting teeth, arranged such that the net translational force on the tool in the plane which is perpendicular to the axis of rotation, resulting from the accumulated resistance of the teeth when rotated against a rotationally symmetrical cavity in which the tool is a snug fit, is approximately balanced.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*